

Point Works GEN II Retardant Spray

Skin Time Retardant Spray for Point Works Gen II

Description

Selleys Point Works Gen II Retardant Spray is specifically formulated to increase the time for *Point Works Gen II* flexible roof pointing to form a skin on the surface. It is available in a 750mL trigger bottle.

Uses

- *Selleys Point Works Gen II Retardant Spray* is recommended for use in hot and windy conditions where skinning of the *Point Works Gen II* may be a problem.

Features/Advantages

- The application of the retardant spray will extend the skinning time of *Point Works Gen II* by approximately 20 minutes (depending on ambient conditions).
- It may be used to retard surface skinning of *Point Works Gen II* in the bucket, or after the pointing has been applied.

Instructions for Use/Application Instructions

The following should only be used as a guide and the installer should apply all Australian Standards, BCA/NZBC requirements, and best practices when pointing roofs with *Point Works Gen II*.

- Spray should be applied before *Point Works Gen II* has skinned over (usually within 10 minutes of opening the bucket or applying the pointing to the roof).
- Use the "spray" setting to apply *Point Works Gen II Retardant Spray* to the surface of before *Point Works Gen II* before it has skinned over.
- Do not use a "stream" setting as the jet may wash out the pointing
- Use as required in order to slow down skinning in the bucket, or as a tooling aid.
- Spray from a distance of approximately 20 centimetres to ensure an even coverage.

Technical Data/Properties

Contact Selleys before using this data for the setting of specifications.

Property	Typical Result
Shelf Life	24 months
VOC	0 g/L

Important Notes/Limitations

- *Point Works Gen II Retardant Spray* should be used as supplied. Do not dilute with water.
- Do not use *Point Works Gen II Retardant Spray* if rain is likely.

Storage

Store unopened bottles below 30°C in a cool dry place away from direct sunlight. Unopened bottles can be stored for 24 months from the date of manufacture.

Safety

No special personal protective equipment required. Wash hands after use. Rubber gloves are recommended if handling often.

Not classified as Dangerous Goods.

Not classified as Hazardous.

Refer to Safety Data Sheet for more detailed information.

Clean up

Spills and tools can be cleaned up with water.

Disclaimer

All information contained in this Product Information Sheet is as accurate and up-to-date as possible. Products can be expected to perform as indicated in this Sheet, so long as application procedures are followed as recommended. Notwithstanding the above, any recommendations made by Selley's or its distributors in relation to this or other products is to be taken as advice only. Selley's makes no representations or warranties that this product will be suitable for use. Subject to any applicable legislation which cannot be excluded (such as the Australian Consumer Law), Selley's takes no responsibility and will not be liable for any failure in performance of this product or any losses, damages, or injuries (consequential or otherwise) arising from the storage, mixing, application or other use of this product or for any representations made by you about the product which have not been approved in writing by Selley's. The buyer assumes all risk and responsibility for the use of this product.

© 2013 **Selley's** Pty Limited

Selley's – a division of DuluxGroup Australia Pty Ltd
1 Gow Street, Padstow, NSW 2211
1300 555 205 (Australia)
0800 735 539 (New Zealand)