

SELLEYS 3 IN 1 CLEAR

Description

Selleys 3 in 1 Clear is an adhesive, sealant and gap filler which uses the latest technology to deliver the most versatile product. It is perfect for virtually any sealing, bonding and filling applications and for virtually any surface. Selleys 3 in 1 is a high strength construction adhesive, a waterproof sealant and no shrink gap filler – all in one.

Product Information

| Packaging | Size | Colour |
|-----------|-----------|--------|
| Cartridge | 300 grams | Clear |

Uses

- Sealing, bonding and filling
- Suitable for wet or dry surfaces
- Interior/exterior use
- Use for glass, metal, timber, brick, concrete, tiles and most plastics[#]

Technical Features

- High strength bond
- Water and weather resistance
- Excellent adhesion
- Highly durable
- Highly versatile
- Interior & exterior
- Paintable
- Non-cracking
- UV Resistant
- Mould resistant
- Fast grab
- Low VOC

Technical Details

| Property | Typical Result |
|--|--|
| Technology | Moisture curing silyl-modified polymer (SMP) |
| Colour | Clear |
| Density | ~1.05 |
| Application Temperature | 5 to 35°C |
| Tooling Time (23°C, 50% R.H.) | ~20minutes |
| Skin Time (23°C, 50% R.H.) | 40 to 50minutes |
| Cure Rate (23°C, 50% R.H.) | 3 to 4mm/24 hrs |
| Slump | 0mm |
| Tensile Strength (DIN 53504) | 1 ± 0.2MPa |
| Shore A Hardness | 40 ± 5 |
| Elongation at Break (DIN 53504) | ~150% |
| Modulus at 100% Elongation (DIN 53504) | 0.6 ± 0.1MPa |
| Movement Capability (ISO9046 modified) | ± 12.5% |
| Service Temperature | 0 to 70°C |
| VOC Content | ~35g/L |
| Indicative data only, not intended for preparation of specifications | |

Surface Preparation

Ensure surface is clean, dry and free from dust, grease, old or crumbling sealant.

SELLEYS 3 IN 1 CLEAR

Directions for Use

Cut tip and attach nozzle. Insert in caulking gun. Cut nozzle to required size.

Adhesive

Apply to one surface, in beads for broad surfaces (every 30cm) or dots for small surfaces. Press surfaces together and allow to cure.

Sealant

Apply product, ensuring it is forced into the joint, with good contact to surfaces. Tool with a soap solution before skinning occurs.

Filler

Apply product into gap. Smooth off with spatula dipped in soapy water. Allow to skin before painting with water-based paints

Tips

For neater joints, mask sides before applying sealant and remove tape before sealant skins.

Larger, heavier items need to be supported until the adhesive cures.

Clean Up

Uncured product may be removed with mineral turps. Cured product can be removed by scraping or sanding or with the help of Silicone Remover.

Storage

Store in cool, dry conditions below 30°C.
Use within 6 months of opening

Limitations

Cannot be painted with solvent based paints. If required, paint with a water-based paint first.

#Not for Polyethylene, Polypropylene or Teflon.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com