

Spakfilla[®] Rapid™

Description

Spakfilla[®] Rapid™ is ready-mixed, lightweight filler that is fast-drying, virtually non-shrinking, non-cracking and needs only one application.

Product Information

Packaging	Size
Tub	180 grams
Tub	260 grams

Uses

Spakfilla[®] Rapid™ is ideal for filling wallboard, wood, masonry, plaster, primed nail heads and plasterboard.

Features

- Paint in 30 minutes
- Moisture and mould resistant
- Easy to sand
- Interior and exterior

Technical Details

Property	Typical Result
Technology	Water based
Appearance	Smooth paste
Colour	White
Sand/Paint Time	Less than 2mm, 30 minutes More than 2mm, 24 hours
Indicative data only, not intended for preparation of specifications	

Surface Preparation

Surface must be clean, dry and free of loose or protruding material – sand surface lightly if necessary.

Directions for Use

1. Using the spatula provided, press filler firmly into hole/crack and smooth off. Spakfilla Rapid exhibits virtually no shrinking, so there is no need to overfill.

2. If necessary, once completely set (30 minutes in thin applications), Spakfilla Rapid can be lightly sanded prior to painting with water-based paints. Minimal sanding required for a smooth finish.

Tips

- Expect longer drying times in cold or humid conditions.
- For oil-based paints, allow 24 hours before painting.
- If filler is found to have stiffened prior to use, stir product. Product that has hardened should be discarded. If still too dry add one teaspoon of water and stir again to desired consistency.
- Application tools may be cleaned with water.
- Before painting, clean dust and loose filler particles using Selleys Sugar Soap or Selleys Super Kleen.
- In exterior applications, protect from rain until dry and painted over with 2 coats of paint.
- Some paints may temporarily discolour when applied over the filler but will revert to the correct colour once dry.

Clean Up

- Uncured product may be removed with water.
- Cured product can be removed by scraping or sanding.

Storage

Keep container closed when not in use.

Limitations

- Do not use on plastic, metal or exterior timber likely to swell/shrink on absorption of water.
- Avoid using below 5°C or in wet conditions.
- Do not nail.
- Do not use where load or compression occurs as product may be crushed e.g. behind a door if the knob touches against the wall.
- Where movement occurs, use **Selleys No More Gaps[®]**.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com